



Expanko Resilient Flooring
1000 East Park Avenue | Maple Shade, NJ 08052
800.345.6202 | sales@expanko.com | www.expanko.com

REZTEC

RECYCLED RUBBER FLOORING

GENERAL DESCRIPTION

Reztec flooring is made from a blend of pre consumer and post consumer waste. By combining these materials, Expanko Resilient Flooring has created a beautiful yet durable and easy to maintain commercial floor. Reztec is available in a variety of standard colors and as well as custom colors.

Benefits:

- FloorScore Certified
- Excellent Acoustical Performance
- Extremely Durable
- Resilient
- Antimicrobial & Antifungal Properties
- Exceeds Industry Standards for Slip Resistance

Material Standards:

Reztec is available in 28 standard colors, Reztec Chunks in 10 standard colors. Custom colors, thicknesses and dimensions are also available.

Dimensions:

- **Rolls:**
 - Width: 48" Wide (4 mm thickness must be ordered in 20' lengths, maximum 60')
 - Thickness: 4 mm, 6 mm, 8 mm and 9.5 mm
- **Tile:**
 - Dimensions: 24" x 24" (even number of tiles must be ordered).
 - Thickness: 4 mm, 6 mm, 8 mm, 9.5 mm
- **InterLoc Interlocking Tiles:**
 - Dimensions: 24" x 24" (outside dimension) 3.5 sq ft per tile
 - Thickness: 8 mm, 9.5 mm

Reztec is an easy to maintain, hard wearing general purpose flooring material suitable for a wide range of installations. A blend of post consumer (recycled tires) and pre consumer waste rubber, Reztec is held together with a urethane binder. This blend is randomly mixed and heated in a cylindrical mold. After the heating process is complete, the cylinder (log) of Reztec is cut into the desired thickness utilizes a circular blade (knife) that "peels" the log. Blade or "knife" marks are inherent and not considered defects. Knife marks may show more in colors with a high percentage of black. Shade variations due to the random mixing process may also be visible in the product. The addition of a sealer will reduce odor and the natural yellowing process of the binder.

For more information visit www.expanko.com or call 800-345-6202.