



Expanko Resilient Flooring
1000 East Park Avenue | Maple Shade, NJ 08052
800.345.6202 | sales@expanko.com | www.expanko.com



LEED RATING SYSTEM

TECHNICAL SUPPORT 800.345.6202

The following are the percentages of post consumer and pre consumer waste for Expanko Reztec and Reztec Chunks Rubber Flooring.

Recycled content of Reztec varies by color. Therefore colors are listed individually. The percentages (listed by weight) are as follows:

Jet:

90% post consumer waste

Jet Blue, Jet Egg, Jet Red, Jet Gray:

72% post consumer waste

6.3% post-industrial waste

Carnival:

63% post consumer waste

9.5% post-industrial waste

Circus, Galaxy, Odyssey:

45% post consumer waste

16% post-industrial waste

Granite, Sasquatch:

22.5% post consumer waste

24% post-industrial waste

Icicles, Marble:

13.5% post consumer waste

27% post-industrial waste

Prairie, Pecan, Peppers, Macadamia:

9% post consumer waste

28.4% post-industrial waste

Avalanche, Billy, Bluegrass, Burnt Sienna, Canary, Carousel, Casino, Confetti, Glacier, Hazelnut, Ice, Pin Ball, Poppy, Smoke, Tangerine:

4.5% post consumer waste

29.9% post-industrial waste

Autumn, Graphite, Velocity:

0% post consumer waste

31.5% post-industrial waste

Reztec EX-Paver and EX-Ground tiles:

90% post consumer waste

The following are areas where Reztec Rubber Flooring helps to achieve LEED credits:

Materials & Resources:

Credits:

MR4.1: Use materials with recycled content such that the sum of the post-consumer recycled content plus ½ post-industrial recycled content constitutes at least 5% of the total value of the materials in the project. (1 point)

MR4.2: Use materials with recycled content such that the sum of the post-consumer recycled content plus ½ the post-industrial recycled content constitutes at least 10% of the total value of the materials in the project. (1 point)

INDOOR ENVIRONMENTAL QUALITY

IEQ 4.1 The VOC content of adhesives and sealants used must be less than the current VOC content limits of South Coast Air Quality Management District Rule #1168 and all sealants used as filters must meet or exceed the requirements of the Bay Area Air Quality Management District Regulations 8, Rule 51 (1 point).

All Expanko adhesives, sealers and polyurethane's meet or exceed the above requirements.

MSDS sheets available upon request.

For more information about Expanko visit: www.expanko.com or call 800.345.6202.