



Expanko Resilient Flooring
1000 East Park Avenue | Maple Shade, NJ 08052
800.345.6202 | sales@expanko.com | www.expanko.com



TECHNICAL SPECIFICATIONS

TECHNICAL SUPPORT 800.345.6202

Suitability: Heavy use Commercial and Residential

Moisture Resistance: Reztec is highly resistant to moisture and is suitable for use in locker rooms and other areas subjected to surface moisture.

Standard Dimensions: Roll Goods - (Maximum Lengths):

<i>Thickness</i>	<i>Dimensions</i>	<i>Square Feet</i>	<i>Weight/ft²</i>
4 mm	4' x 58'	232	1.2 lb
6 mm	4' x 38'	152	1.8 lb
8 mm	4' x 29'	116	2.3 lb
9.5 mm	4' x 25'	96	2.7 lb

- Tiles: 24" x 24"
- InterLoc interlocking tiles: 34.5" x 34.5"

Thickness: 4 mm, 6 mm, 8 mm, or 9.5 mm. InterLoc tiles are available only in 8 and 9.5 mm thickness. Minimum quantities may be required.

Density: ASTM D-792 Greater than 78 lbs/ft³.
Aging Resistance: ASTM D-750 No Change
Shore Hardness: ASTM D-2240 60 +/- 5
Flammability: ASTM E-648 Class I
Flame Spread: ASTM E-84 Class B
Smoke Developed: ASTM E-84 Passes <450
Ozone Exposure: ASTM D-1149-86 No adversities
Storage: Rolls on end, minimum 55° F. Less than 50% humidity

* The above listed specifications are for 70% or greater EPDM formulations. Test Results will vary for those products with greater than 30% SBR content.

Reztec is a naturally resilient product with unparalleled durability, suitable for both commercial and residential installations. As with any flooring product, Reztec must be kept clean and dry to ensure its beauty throughout the life of the floor. Like any naturally pigmented product, Reztec colors can vary slightly between lots.

For more information visit www.expanko.com or call 800-345-6202.