



TECHNICAL SPECIFICATIONS - UNDERLAYMENT

TECHNICAL SUPPORT 800.345.6202

Suitability: Commercial and Residential

Moisture Resistance: Reztec is highly resistant to moisture and is suitable for use in locker rooms and other areas subjected to surface moisture.

Standard Dimensions: Roll Goods - (Maximum Lengths):

<i>Thickness</i>	<i>Dimensions</i>	<i>Square Feet</i>
2 mm	4' x 50'	200
5 mm	4' x 25'	100
10 mm	4' x 25'	100
12 mm	4' x 25'	100

Thickness: 2mm, 5mm, 10mm or 12mm

Density:	ASTM D3574	47-50 lbs/cu.ft.
Compression Resistance	ASTM D3574	65 @25% (CFD)
Compression Set	ASTM D3574	14 @25%
Flammability:	CPSC STD. FF 1-70	PASSED
R-Value:	ASTM C518	0.14
Tensile Strength:	ASTM D412	120 psi
Storage:	Rolls on end @ temperature between 70F & 95F	

Reztec is a naturally resilient rubber product with unparalleled durability, suitable for both commercial and residential installations. As with any flooring product, Reztec must be kept clean and dry to ensure its beauty throughout the life of the floor. Like any naturally pigmented product, Reztec colors can vary slightly between lots.

For more information visit www.expanko.com or call 800-345-6202.